



SF-3050

- Sapphire™ GNSS Engine
 - 66 Channel GNSS Receiver
- Multi-Constellation Support
 - GPS, GLONASS, GALILEO
- Software Upgradeable Receiver
- Integrated StarFire™ with decimeter global accuracy
- Ultra RTK™ (GPS + GLONASS)



A John Deere Company

www.navcomtech.com

NavCom's SF-3050 family of integrated StarFire™/RTK Extend™ Receivers provide decimeter-level position accuracy, anywhere in the world, anytime.



Powered by the new Sapphire™ Engine, the SF-3050 provides 66 channel tracking, including multi-constellation support for GPS, GLONASS and Galileo. It also provides patented interference rejection and anti-jamming capabilities.

Offering the "freedom to choose," the SF-3050 is fully upgradeable allowing users to upgrade from a single frequency receiver to multi-frequency or anything in between with just a software bundle upload, saving users the expense of purchasing a new receiver. This flexible framework makes the SF-3050 ideal for any application.

FEATURES

- "All-in-view" parallel tracking with 66 channels
- SBAS (WAAS/EGNOS/MSAS/GAGAN) tracking
- Built-in StarFire receiver
- L1, L2, L5, G1, & G2 full wavelength carrier phase tracking
- C/A, P1, P2, L2C, L5, G1 & G2 code tracking
- Software upgradeable for Galileo signal reception (E1, E5a)
- High sensitivity / low signal level tracking
- Fast acquisition / re-acquisition
- Superior interference suppression (both in-band & out-of-band)
- Patented multipath rejection
- RTK Extend™
- StarFire Over the Air (OTA) Licensing Capable
- Minimal data latency
- Data message formats
 - NMEA-0183: ALM, GBS, GGA, GLL, GRS, GSA, GST, GSV, RMC, RRE, VTG, ZDA, NCT proprietary
 - Differential Correction: RTCM 2.3 and 3.0, SBAS, and StarFire (proprietary)
 - RTK Correction: CMR/CMR+, RTCM, NavCom Proprietary UltraRTK™
 - Receiver Control: NavCom Proprietary commands (ASCII)
- Configurable as RTK base or rover
- Programmable output rates
- Event marker input
- 1 PPS output
- Communication Ports: 2 x RS232 (1 - Changable to RS422), 1 x USB 2.0 (Host or Device), Bluetooth™ and Ethernet (10T/100T)
- 2GB Internal Data Storage



Sea and Land Technologies Pte Ltd

65 Tuas Avenue 1
Singapore 639508
Website: <http://www.sea-landtech.com.sg>

Tel : +(65) 6518 0777
Fax : +(65) 6563 0366
Email: enquiry@sea-landtech.com.sg

SPECIFICATIONS

PERFORMANCE⁽¹⁾

- Accuracy (RMS)

	Horizontal / Vertical
RTK: <40km	1cm + 0.5ppm / 2cm + 1ppm
StarFire	<10cm / <15cm
Code DGPS: <200kms	45cm + 3ppm / 90cm + 3ppm
Velocity:	0.01ms
RTK Extend (<15min)	3cm + 1ppm / 6cm + 2ppm
- User programmable output rates:

Position Velocity Time:	1Hz, 5Hz, 10Hz, 25Hz, 50Hz, 100Hz
Raw data:	1Hz, 5Hz, 10Hz, 25Hz, 50Hz, 100Hz
- Data Latency:

Position Velocity Time:	< 10ms at all rates
Raw measurement data:	< 10ms at all rates
- Time-to-first-fix:

Cold / Warm / Hot	< 60s / < 50s / < 20s
-------------------	-----------------------

 (typical values measured per ION-STD 101)
- Dynamics (Speed & altitude are restricted by export laws):

Acceleration:	up to 6g
Speed:	< 515 m/s (1000knots)
Altitude:	< 18.3 km (60,000ft)

PHYSICAL/ENVIRONMENTAL

- Size (L x W x H): 164mm x 117mm x 60mm (6.47in x 4.60in x 2.37in)
- Weight: 0.5kg (1.1lbs)
- Power:

Input:	AC/DC Adapter 110/220VAC, 12VDC Nominal 0.5A (9.0V to 32VDC)
--------	--------------------------------------------------------------
- Temperature (ambient):

Operating:	-40° to +70° C (-40° to +158° F)
Storage:	-40° to +85° C (-40° to +185° F)
- Humidity: 95% non-condensing
- Tested in accordance with MIL-STD-810F for low pressure, solar radiation, humidity, salt fog, shock and vibration
- Rated IP67 (dust tight/waterproof) in accordance with IEC 60529
- Tested in accordance with FCC/CE regulations for electromagnetic interference
- Connectors:

Port	Antenna	COM1/LAN	COM2/USB	Power
Connector Type	TNC (female)	9 pin female circular	9 pin female circular	9 pin male circular
I/O Function	Antenna Input	Ethernet COM1 (RS232)	USB 2.0 COM2 (RS232/RS422)	PWR Input

⁽¹⁾ Performance dependent on location, satellite geometry, atmospheric conditions and GNSS corrections.

Technical specifications subject to change at NavCom's discretion



Rear Panel of the SF-3050