

# SGB2000

SOLID STATE GYROCOMPASS

## A high performance solid state gyrocompass.

With more 100 years of experience in navigation technology, Teledyne TSS Ltd has produced a gyrocompass that meets the needs of customers requiring a cost effective primary navigation solution. With no moving parts and no regular maintenance required the SGB2000 offers a real alternative to mechanical gyrocompasses with low through life costs. The SGB2000 has been designed to satisfy the demand for a rugged, high performance solid state gyrocompass by using high grade inertial sensing elements with exceptionally high shock-rating and MTBF.

The SGB2000 will be available with IMO Wheelmark and HSC certification and has a flexible interface allowing easy connectivity to existing ships systems. A comprehensive range of repeaters are available from Teledyne TSS to complement the SGB2000.

The extremely accurate and stable heading can be maintained during turns of up to 200 degrees per second making the system ideal for use on fast survey craft and in river/harbour environments. The SGB2000 is available in both surface and subsea housings allowing the unit to be used in a range of environments and applications.



- Surface variant IMO and Wheel Mark certified
- Maintenance free ring laser gyros and accelerometers with MTBF in excess of 300,000 hours
- Latitude and speed corrected
- 3000 m subsea housing available with horizontal or vertical mounting for ROV and subsea structure mounting
- Multiple configurable I/O channels
- Fast settling time
- Low power consumption



# SGB2000

SOLID STATE GYROCOMPASS

## SGB2000

### TECHNICAL SPECIFICATIONS

<b>Heading</b>	Dynamic accuracy	<0.5° sec/lat RMS
	Setting time	<15 minutes
	Data latency	<3 ms
	Resolution	0.01° (or as dictated by O/P packet format)
<b>Roll and Pitch</b>	Accuracy	<0.2 RMS
	Range	±90°
	Limits	None
	Axis alignment	<0.005°
	Data latency	<3ms
	Resolution	0.01°
<b>Data Parameters</b>	Serial outputs	3 configurable I/O Channels
	Data protocols	RS232 and RS422
	Data output rate	Up to 200 Hz
	Baud Rate	1200 – 38,400
	Data Bits	7 or 8
	Stop Bits	1 or 2
	Parity	None, even or odd
	Data output formats	TSS1, TSS HHRP, TSS1 + NMEA HDT, TSS3, Simrad EM1000, Simrad EM3000, Atlas, NMEA PRDID, BMT1, Polled, User configurable
<b>Aiding</b>	GPS	NMEA 0183 GGA and VTG
<b>Environmental</b>	Ambient operating temperature	-10°C to +55°C operational, -20°C to +70°C storage
	Shock (survival)	22g
	Housing: Surface Subsea 3000m	IP65 rated, aluminium Aluminium
<b>Physical</b>	Dimensions: Surface Subsea	380mm (l) x 240mm (w) x 183mm (h) (including connectors) 235 (d) x 350mm (h) (including handles & connectors)
	Weight: Surface Subsea	13 kg 20Kg in air; 12.8Kg in water
<b>Electrical</b>	Power requirement	18-36V DC
<b>Regulatory Approval</b>	CE, EMC, High Speed Craft	
<b>MTBF</b>	System	>30,000 hours
	RLGs and Acclerometers	>300,000 hours
<b>Warranty</b>	24 months (including parts and labour)	

*Due to continuous development, specifications may vary from those listed above.*

WORLD LEADERS IN MARINE NAVIGATION



**TELEDYNE TSS**  
A Teledyne Technologies Company



Certificate Number: 160263  
BS EN ISO 9001 : 2000

### Sea and Land Technologies Pte Ltd

65 Tuas Avenue 1  
Singapore 639508  
Email: [enquiry@sea-landtech.com.sg](mailto:enquiry@sea-landtech.com.sg)  
Website: <http://www.sea-landtech.com.sg>

Tel : +(65) 6518 0777  
Fax : +(65) 6563 0366