

## XF102 DGPS Receiver

### Superior accuracy for handheld mapping



#### XF102

Hemisphere GPS XF100™ Series DGPS Receivers for ruggedized handheld computers provide superior accuracy and performance. The XF102™ is designed specifically for the TDS Nomad™ (not included). The rugged Compact Flash adapter and smart antenna module simplify field use even in the most demanding environments.



Powered by **Crescent**

The latest Hemisphere GPS products are powered by Crescent Receiver Technology, the future of precision GPS.

### Key XF102 Advantages

- Crescent® GPS technology for superior sub-meter accuracy
- Optional external antenna for additional accuracy
- COAST™ Technology maintains accuracy during temporary loss of differential signal
- Exclusive e-Dif® extended differential option available
- Fully integrated, robust design matched to the host handheld PC
- Easy to use - just connect to handheld and go
- Low power consumption conserves handheld battery power

## XF102 DGPS Receiver

### GPS Sensor Specifications

Receiver Type: L1 (C/A), with carrier phase smoothing  
Channels: 12-channel parallel tracking (10-channel when tracking SBAS)  
SBAS Tracking: 2-channel, parallel tracking  
Update Rate: 1 Hz

\*Horizontal Accuracy: < 0.4 m RMS confidence (DGPS)\*  
< 1.8 m RMS confidence (autonomous, no SA)\*  
< 0.3 m RMS confidence (DGPS, external antenna)\*

Cold Start: 60 s (no almanac or RTC)  
Warm Start Time 1: 45 s (valid almanac, no RTC)  
Warm Start Time 2: 35 s (valid almanac and RTC)  
Hot Start Time: 20 s typical (valid almanac, RTC and two hours since last fix)  
Reacquisition: <1 s

\* Depends on multipath environment, number of satellites in view, satellite geometry, and ionospheric activity

### Environmental

Operating Temperature: -30°C to +60°C (-25°F to +140°F)  
Storage Temperature: -40°C to +70°C (-40°F to +158°F)  
Humidity: MIL-STD-810 F, Method 507.4

### Mechanical

Dimensions: 101 L x 97 W x 35 H mm (4.0 L x 3.8 W x 1.4 H inches)  
Weight: 300 g (<10.6 oz)  
Status Indication (LED): 1 LED indicating power  
Antenna Connector: SMB, female



### Authorized Distributor:



**Sea and Land Technologies Pte Ltd**  
65 Tuas Avenue 1, Singapore 639508  
Tel : +65 6518 0777 Fax : +65 6563 0366  
enquiry@sea-landtech.com.sg  
www.sea-landtech.com.sg

Copyright © 2009 Hemisphere GPS. All rights reserved. Specifications subject to change without notice. Hemisphere GPS and the Hemisphere GPS logo and Crescent and the Crescent logo are trademarks of Hemisphere GPS.

Nomad is a registered trademark of Tripod Data Systems. Microsoft, Windows, and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Other brand names and trademarks are property of their respective owners.