



Portable 2 Divers Air Control and Depth Monitoring Unit High Pressure inlet to Low Pressure Outlet SALTAIR MODEL 3885



The S.A.L.T 3885 Two Divers H.P portable box panel is design for easy mobilization. The box is water proof & rugged. It comes with 2 nos of H.P inlet as ONE working another ONE acts a backup or Emergency supply. The systems basically is a simple layout for supervisor to operate. It comes with a crossover valve that act as a Emergency supply to another Diver.



High Pressure Section:

- Inlet Connection- JIC 4 [2 nos]
- Inlet Pressure Range- 0-5000psi
- Stainless Steel Needle Valve.
- Pressure Gauges 2 ½".
- Non Return Valve Stainless Steel.
- High Pressure Regulator c/w over pressure relief valve. [2 nos]

Low Pressure Section:

- Pressure Gauges 2 ½".
- Non Return Valve Brass.
- Ball Valve Brass.
- Needle Valve Brass.
- Bulkhead Brass.
- Pneumo Gauge 4 ½" Dial 0-250 FSW Accuracy 0.25% c/w Over Pressure Relief Valve. [2 nos]
- Diver's Pneumo Outlet- JIC 4 [2 nos]
- Diver's Air Outlet- JIC 8 [2 nos]
- Stainless Steel Tubing- ¼" & ½".

Weight: Approximately – 50kg
Dimension: 640 mm x 520 mm x 460 mm.
Aluminium Panel Powder Coated-[White]