



## SALT 5-CYLINDER SCUBA REPLACEMENT PACK Model SLT 5000 SRP



The SALT 5 cylinders S.R.P is designed for shallow diving operations. The system comes with a 3 Divers outlet. (2 working and 1 standby) There is a crossover valve included in the panel for Emergency or switch over of air supply from individual Diver. High Pressure Regulators are fitted onto the panel to allow H.P Air Upstream to be regulated to Downstream for a safe pressure breathing. The system comes with a L.P Air supply inlet as a backup Air supply to the divers

### High Pressure Section:

- Inlet Charging Connection- JIC 4 [ 1 nos]
- Inlet Pressure Range- 0-5000 psi.
- Stainless Steel Needle Valve.
- Pneumo Gauge 6" Dial 0- 250 FSW Accuracy 0.25% c/w Gauge Protector [ 3 nos]
- Pressure Gauge 2 1/2".
- Non Return Valve Stainless Steel.
- High Pressure Regulator c/w Over Pressure Relief Valve [ 3 nos]

### Optional Items:

- 1 x C Vision Video camera and light with
- 1 x 2 Divers Communication .
- 2 x Diving Umbilical 50m
- 1 x Diving Umbilical 70m Standby
- 3 x KMB 28B Full Face Mask
- 1 x HP Breathing Air Compressor
- 1 x Back up battery with DC/AC converter

### Low Pressure Section:

- Inlet Connection- JIC 8 [ 1 nos]
- Inlet Pressure Range- 0-600 psi.
- Pressure Gauge 2 1/2".
- Non Return Valve Brass.
- Needle Valve Brass.
- Ball Valve Brass.
- Bulkhead Brass.
- Pneumo Outlet- JIC 4 [ 3 nos]
- Outlet Diver's Air Supply - JIC 8 [ 3 nos]
- Stainless Steel Tubing- 1/4" & 1/2".

Weight: Approximately 970kg

Dimension: 2400mm x 109mm x 13mm

Material: Mild Steel

Aluminum Panel Powder Coated [ Blue]

Panel Dimension: 795mm x 795mm x 3mm